

Design Features

- Materials
Ductile Iron (80-55-06)
- Design Load
Extra Heavy Duty
Class F
- Open Area
61% (107.5in² Lin. Ft.)
- Coating
Dipped
Hot Dipped Galv. (optional)

Certification



- ASTM A536-80
- Country of Origin: USA

Fits

- FP1200 Trench Drain
Bolt: 3/8"-16 - 2 1/2"
Washer: 3/8"

Disclaimer

Weights (lbs./kg) dimensions (inches/mm) and drawings provided for your guidance. We reserve the right to modify specifications without prior notice.



Airport, Docks and heavy traffic areas. Designed for a distributed pressure of 202,320 lbs (900kN).

Meets the following Standards & Specifications

- DIN 19580 / DIN EN 1433 Drainage Channels for Vehicular and Pedestrian Areas
- AASHTO H-25 per AASHTO M-306 Drainage, Sewer, Utility, and Related Castings
- Federal Aviation Administration (FAA) Advisory Circular AC 150/5320-6E Appendix 3. Design of Structures for Heavy Airplanes

	BY	DATE	WEIGHT
DRN	JRP	1/15/18	#66
MOD	JRP	1/16/18	
ENG			
APR	JRP		
SCALE			
NOT TO SCALE			
DRAWING NUMBER			
TDS-1246			
PART NUMBER			
FG1246			

TRENCH DRAIN SYSTEMS

www.TrenchDrainSystems.com
PO Box 377 • Fremont, OH 43420 USA
(610) 638-1221

DRAWING DESCRIPTION

DUCTILE IRON GRATE
14.6" x 24"